



CAMIE-CAMPBELL, INC.
Aerosol and Bulk Industrial Specialty Chemicals



2651 Warrenville Road • Downers Grove, IL 60515
Phone: 800-325-9572 • Fax: 314-968-0741
E-mail: info@camie.com • www.camie.com

CAMIE 573 PRODUCT DATA SHEET

Camie 573 High Performance Adhesive, Low VOC.

Unique formula prevents soak in of the adhesive on porous surfaces. It offers the user very high coverage with a fast tack time for general purpose bonding of a wide variety of substrates.

Applications	Camie 573 High Performance Adhesive is recommended for paper, cardboard, label work and polyurethane foam. It can be used for case sealing, palletizing, and labeling. When properly used, Camie 573 will not degrade styrofoam.
Container Size	20 Fluid oz. Container
Product Description	High Performance Adhesive
Net Weight	13 Ounces
Cans Per Case	12
Case Dimensions Inches	10 3/4 L x 8 3/16 W x 10 3/16 H
Case Weight	14 Pounds
Cases Per Pallet	72 Cases
Appearance	White
Odor	Solvent
Solvent System	Heptane, Acetone and Methyl Acetate
Propellant	Dimethyl Ether
Bond Time	20 Seconds to 2 Minutes
Heat Resistance	120° F
Solids	34%
Spray Pattern	Fan Mist
VOC %	28.4%
VOC Compliant for CA & OTC	Yes
Aerosol Flammability Level	Level 3 Aerosols
Warranty Period	One Year From Date of Shipment
Food packaging Adhesive Complies with 21CFR 175.105	No
DOT Proper Shipping Name	Limited Quantity for domestic ground shipment (See SDS for additional shipping information)



CAMIE 573

In as much as CAMIE-CAMPBELL, INC. has no control over the use to which others may put the material, it does not guarantee that the same results described herein will be obtained. Each user should make his own tests to determine the material's suitability for his own particular use.