



CAMIE-CAMPBELL, INC.
Aerosol and Bulk Industrial Specialty Chemicals



2651 Warrenville Road • Downers Grove, IL 60515
Phone: 800-325-9572 • Fax: 314-968-0741
E-mail: info@camie.com • www.camie.com

CAMIE 590B FAST TACK UPHOLSTERY ADHESIVE

FOR USE ON URETHANE FOAM, FABRICS, AND SUPPORTED VINYL,
DESCRIPTION: A high solids synthetic rubber adhesive which can be dispensed through any low pressure air sprayer. It gives quick tack forming a strong bond and soft glue line when bonding, splicing or pinching urethane foam.

Color	Light Amber or Red
Base	Synthetic Resin & Styrene Copolymer Blend
Solvent System	Heptane, Acetone, Methyl Acetate & PCBTF
Viscosity	10-500 CP
Solids	40% +/-1.5%
Density	1.0-1.11
Coverage	Approximately 400 to 500 square feet
Heat Resistance	Maximum temperature of cured adhesive 130°F
Bonding Time	30 seconds to 5 minutes***
Container Size	5 gal pails & 52 gallon drums
Suitable Solvents for Cleanup	Mineral Spirits
Odor	Strong Solvent
Flammability	Extremely Flammable
Physical and Chemical Resistance	Good resistance to oxidation and moisture
Application, Uses and Suggestions	Formulated for use in the foam & fabric trade for a quick tack, strong bond and soft glue line. 590 works well to affix Urethane foam, fabric, and paper to metal, wood etc. This product requires the use of an air spray gun.
VOC Compliant CARB/OTC:	<45.4 g/l less water and exempt
24 HR. MEDICAL EMERGENCY:	1-866-836-8855



Also available in 1 Gallon Pail
Clear or Red

CAMIE 590B

*** applied to both surfaces and Bonding times will depend on ambient temps and substrates as well as air Psi

**See label for First Aid and additional Precautionary Statements.
KEEP OUT OF REACH OF CHILDREN. CONSULT SDS BEFORE USING**



In as much as CAMIE-CAMPBELL, INC. has no control over the use to which others may put the material, it does not guarantee that the same results described herein will be obtained. Each user should make his own tests to determine the material's suitability for his own particular use.